



FH6-Tipper





FH6-Tipper

Technical Specifications	
Cab and General	
Driving side	LHD & RHD
Seating capacity:	2+1
Engine System	
Model:	YZ4105ZLQ
Type:	4 cylinder, diesel, turbo inter-cooled
Max. Output (Kw(rpm)):	90(2800)
Torque (N.m):	350(1600)
Displacement (cc):	4087
Compression ratio:	17.5:1
Transmission and clutch	
Gearbox	6 speed manual, with synchromesh
Clutch:	Dry, single plate, hydraulic control
Performance	
Drive:	4 x 2
Speed (km/h):	105
Gradeability (%):	30%
Dimensions	
Length:	5775
Width:	2330
Weight:	2420
Cargo body (mm):	
Length:	3600
Width:	2076
Height:	700
Tread (m):	
Front:	1675
Rear:	1485
Minimum turning (m):	
Ground clearance (mm):	213
Weight	
Laden (kg):	8600
Kerb weight (kg):	2600
Payload (kg):	6000
Wheels and tyres	
Wheel base (mm):	3800
tyre size:	8.25 – 16
Gear Ratios	
Gear box transmission gear ratio:	
1st:	6.32
2nd:	3.19
3rd:	2.26
4th:	1.39
5th:	1
6th:	0.79
Rear axle gear ratio:	5.29
Brake system	
Brake System:	Air brakes
Chassis frame	
Front axle:	I-Beam construction
Rear axle:	Full float, single reduction
Steering:	Power assisted
Suspension	
Front & Rear:	Leaf spring, hydraulic absorber
Fuel Tank	
Capacity (L):	100
Electrical System	
System voltage (V):	24V
Generator (A):	500W/1000W

TRANSVEHCO

Walvis bay – Namibia

RAM Building, Circumferial rd, Walvis bay
Tel: +264 64 202 613

Oshikango – Namibia

Main rd, Oshikango
Tel: +264 65 264 813/491

Kasembulase - Zambia

Congo rd, Kasembulesa
Tel: +260 96 107 2400